




# TECHNICAL DATA SHEET

NAME	REFERENCE
HIGH SPEED HAND DRIYER TIFON	<b>AA25050</b>
DETAILS	
<p>CONSTRUCTION IN POLICARBONATE-ABS. CONTEINS ANTIBACTERIAL ADDITIVE TO PREVENT THE GROWTH AND TRANSMISSION OF BACTERIA</p> <p>HEPA FILTER EXTRA SIZE. AVOIDS BACTERIA ABSORTION 99,95%</p> <p>AUTOMATIC EVAPORATOR SYSTEM</p> <p>SWITCH OFF AUTOMATIC AFTER 30 SEC.</p> <p>ENERGY SAVING SYSTEM: THERMAL RESISTANCE SWITCH OFF IF ROOM TEMPERATURE EXCEED 25°C</p> <p>LED INFORMATION PANEL</p> <p>COMPACT DIMENSIONS, HIGH PERFORMANCE, LOW SOUND RATIO, HIGH SPEED 540 KM/H</p>	
	<b>EAN CODE</b>
	8427950350566

CHARACTERISTICS				
<b>NET</b> (Without packaging)	<b>DIMENSIONS (mm)</b>	HIGHT: 540	WIDTH: 320	DEPTH: 180
	<b>WEIGHT (Kg)</b>	6,650		
<b>GROSS</b> (With packaging)	<b>DIMENSIONS (mm)</b>	HEIGHT: 270	WIDTH: 590	DEPTH: 375
	<b>WEIGHT (Kg)</b>	7,450		
<b>MATERIALS</b>	POLICARBONATE-ABS WITH ANTIBACTERIAL ADDITIVE. INTERNAL COMPONENTS V0			
<b>COLOR / FINISH</b>	WHITE			
<b>ELECTRICAL FEATURES</b>	VOLTAGE: 220-240 V FRECUENCY: 50-60 Hz. CONSUMPTION: 5,2 A - 7,5 A MOTOR POWER: 1000 W HEATING ELEMENT POWER: 500 W EVAPORADOR POWER: 50 W TOTAL POWER: 1550 W MOTOR RPM: 30.000		AIR SPEED: 540 Km/H EFFECTIVE AIR FLOW: 220 m³/H SOUND PRESSURE: 65,6 dBA AIR TEMPERATURA: 40° C ELECTRICAL INSULATION: CLASE II CERTIFICATES: SGS - CE PROTECTION GRADE: IP23 MOTOR TYPE: Universal	
<b>NOTES</b>	Drying time 10 seconds			
<b>PACKAGING</b>	SINGLE UNIT PACKAGING		<b>Approved by: Quality Control Dept.</b>  <b>DATE:</b> 12/01/2017	