




TECHNICAL DATA SHEET

NAME	REFERENCE
HAND DRYER TIFON, INOX BRIGHT FINISH	AA26550
DESCRIPTION	
<p>MADE OF ANTIBACTERIAL ABS OF HIGH QUALITY AND RESISTANCE FRONT COVER MADE OF INOX STEEL AISI 304</p> <p>LARGE HEPA FILTER H14, LONG LASTING LIFE</p> <p>AUTOMATIC EVAPORATION OF WATER COLLECTED</p> <p>SECURITY TIMER, DISCONNECTS AUTOMATICALLY</p> <p>WHEN ROOM TEMPERATURE EXCEEDS 25°C: HEATING ELEMENT IS SWITCHED OFF AUTOMATICALLY</p> <p>LUMINOUS DISPLAY WITH ALARMS TO INFORM OF ANY PROBLEMS</p> <p>REDUCED DIMENSIONS, ENERY SAVING, AIR SPEED 540 km/h</p>	
	EAN CODE
	8427950356087

CHARACTERICTICS				
NET (without packaging)	DIMENSIONS (mm)	HEIGHT: 540	WIDTH: 320	DEPTH: 180
	WEIGHT (Kg)	8,030		
GROSS (with packaging)	DIMENSIONS (mm)	HEIGHT: 605	WIDTH: 380	DEPTH: 270
	WEIGHT (Kg)	9,300		
MATERIALS	FRONT COVER: STAINLESS STEEL INOX AISI 304 PLASTIC PARTS: ANTIBACTERIAL ABS +PC+ PBT V0			
COLOUR / FINISH	FRONT COVER: BRIGHT FINISH PLASTIC PARTS: PAINTED IN SILVER GREY			
ELECTRICAL FEATURES	VOLTAGE: 220-240 V		*AIR SPEED: 540 Km/HOUR	
	FRECUENCY: 50-60 Hz.		EFFICIENT AIRFLOW: 220 m ³ /HOUR	
	CONSUMPTION: 5,2 A - 7,5 A		*SOUND PRESSURE: 65,6 dBA	
	MOTOR POWER: 1000 W		AIR TEMPERATURE: 40 ^o C	
	AIR HEATING ELEMENT POWER: 500 W		ELECTRICAL INSULATION: CLASS II	
	EVAPORATOR HEATING ELEMENT P: 50 W		CERTIFICATIONS: GS - CE - SGS	
	TOTAL POWER: 1550 W		PROTECTION DEGREE: IP21	
	MOTOR RPM: 30.000		TYPE OF MOTOR: universal motor	
COMMENTS	DRYING TIME : 10 seconds			
PACKAGING	SINGLE UNIT PACKAGING.		Approved by: Quality Control Dept.	
			DATE: 17/01/2019	

*Sound pressure measured at a distance of 2 m outdoors.

*Air speed is measured by means of anemometric probe placed at air outlet.

Tests have been carried out following UNE rules at the laboratories of the Technical University of Valencia