




TECHNICAL DATA SHEET

NAME	REFERENCE
HAND DRYER TIFON, INOX SATIN FINISH	AA27550
DESCRIPTION	
MADE OF ANTIBACTERIAL ABS, OF HIGH QUALITY AND RESISTANCE FRONT COVER MADE OF INOX STEEL AISI 304	
LARGE HEPA FILTER H14, LONG LASTING LIFE	
AUTOMATIC EVAPORATION OF WATER COLLECTED	
SECURITY TIMER, DISCONNECTS AUTOMATICALLY	EAN CODE 8427950356094
WHEN ROOM TEMPERATURE EXCEEDS 25°C: HEATING ELEMENT IS SWITCHED OFF AUTOMATICALLY	
LUMINOUS DISPLAY WITH ALARMS TO INFORM OF ANY PROBLEMS	
REDUCED DIMENSIONS, ENERGY SAVING, AIR SPEED 540 km/h	

CHARACTERISTICS				
NET (without packaging)	DIMENSIONS (mm)	HEIGHT: 540	WIDTH: 320	DEPTH: 180
	WEIGHT (Kg)	8,030		
GROSS (with packaging)	DIMENSIONS (mm)	HEIGHT: 605	WIDTH: 380	DEPTH: 270
	WEIGHT (Kg)	9,300		
MATERIALS	FRONT COVER: STAINLESS STEEL INOX AISI 304 PLASTIC PARTS: ANTIBACTERIAL ABS +PC+ PBT V0			
COLOUR / FINISH	FRONT COVER: SATIN FINISH PLASTIC PARTS: PAINTED IN SILVER GREY			
ELECTRICAL FEATURES	VOLTAGE: 220-240 V	*AIR SPEED: 540 Km/HOUR		
	FREQUENCY: 50-60 Hz.	EFFECTIVE AIRFLOW 220 m ³ /HOUR		
	CONSUMPTION: 5,2 A - 7,5 A	*SOUND PRESSURE: 65,6 dBA		
	MOTOR POWER: 1000 W	AIR TEMPERATURE: 40° C		
	AIR HEATING ELEMENT POWER: 500 W	ELECTRICAL INSULATION: CLASS II		
	EVAPORATOR HEATING ELEMENT P: 50 W	CERTIFICATIONS: GS - CE - SGS		
	TOTAL POWER: 1550 W	PROTECTION DEGREE: IP21		
	MOTOR RPM: 30.000	TYPE OF MOTOR: Universal motor		
COMMENTS	DRYING TIME 10 seconds			
PACKAGING	SINGLE UNIT PACKAGING.		Approved by: Quality Control Dept.	
			DATE: 17/01/2019	

*Sound pressure measured at a distance of 2 m outdoors.

*Air speed is measured by means of anemometric probe placed at air outlet.

Tests have been carried out following UNE rules at the laboratories of the Technical University of Valencia