



VACUUM CLEANER - SPECIAL SOLUTIONS - HIGH FILTRATION

GS 1/33 H ISO5 ULPA





WATER LIFT

AIRFLOW

TANK CAPACITY

2870

EXCLUSIVE FEATURES

ONE STEP AHEAD

- **AP TUBE**
- **INNOVATIVE GASKET**
- **STRONG HOOKS**
- **SCREWING CONNECTION**
- **PCB PREFILTER**
- **MICROFIBER BAG**
- LATCHING BLOCKING **SYSTEM**
- **4 STAGES OF HIGH FILTRATION**
- **H CLASS CERTIFICATION FOR HAZARDOUS DUST RECOVERY**
- ISO5 CLASSIFICATION FOR **CLEANROOM**
- **ELECTROMEDICAL COMPLIANCE**
- **ULPA U15 FILTRATION WITH AEROSOL CARTRIDGE LEAK**
- **DOWNSTREAM HEPA H14 CARTRIDGE**
- **SAFETY DISPOSAL SYSTEM**



MOST FREQUENTLY USE

FACILITY MANAGEMENT

INNOVATIONS



COMMUNITIES

HORECA

SCHOOLS



SPECS



ULPA U15 TESTED UPSTREAM CARTRIDGE



LATCHES BLOCKING SYSTEM FOR STEADY TRANSPORT



INTEGRATED CAP FOR SAFE DISPOSAL



TECHNICAL DATA

GS 1/33 H ISO5 ULPA

Code		ASD013903	
PERFORMANCE			
Usage		ONLY DRY	
Motor		1	
Power	W	1300	
Voltage	V	220-240	
Waterlift	mmH ₂ 0	2870	
Airflow	m³/h	210	
Tank Capacity	l	33 / stainless steel AISI 304	
Cable length	m	8,5	
Filtering surface	cm ²	12.000	
Sound Pressure Level	dB(A)	64	
Diameter of accessories	mm	36	
Dimensions (LxWxH)	mm	380x380x650	
Weight	Kg	12	

STANDARD EQUIPMENT

CODE: **MICOFIBER BAG CLASS M**



CODE: TBFX00704 **FLEXIBLE HOSE 2M** Ø36 mm



CODE: MPVR00141 SMALL TOOL Ø36 mm



ULPA U15 UPSTREAM CARTRIDGE

CODE: FTDP00844



CODE: LAFN28238 (1 PC) **ALUMINIUM PLASTIC TUBE** 50 cm Ø36 mm (MACHINE COMES WITH 2 PCS)



CODE: SPPV28243 **ROUND BRUSH Ø36 mm**



CODE: FTDP00592 **HEPA CARTRIDGE H14** DOWNSTREAM 2.300 cm²



CODE: LAFN85073 **HANDLE WITH AIR** REGULATOR Ø36 mm



CODE: FTDP40016 **POLYCARBON PREFILTER FOR CARTRIDGE**



CODE: SPPV01771 **DUST FLOOR TOOL** Ø36 mm



CODE: RCVR00936 **COMPLETE CAP FOR INLET** (FOR SAFE DISPOSAL)



CODE: SPPV28242 FLAT LANCE Ø36 mm







CODE: KTRI05204 MICROFIBER BAG CLASS M SET OF 10 PCS



CODE: MISC00019 **SAFE DISPOSAL** POLYTHENE BAG 0,1X80X100mm



CODE: FSVR00152 SAFE SEALS FOR BAG CLOSING



CODE: MISC00025 **ENDLESS BAG 20mt WITH** SAFE SEALS

